



**Troffer**

**GTC24**

600mm Dia x 120mm  
24" nom.x 4.5" nominal



Project: \_\_\_\_\_  
Type: \_\_\_\_\_  
Catalog No: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Specifiers: \_\_\_\_\_  
Line Notes: \_\_\_\_\_

**Ordering Guide**

Series	Mount Method	CCT	Wattage	Control Type	Input Voltage	Wet/Dry	Body Finish
GXXXX	X	XX	XXW	X	XXXV	XXXXX	XXXXX
	<p><b>T</b> T-Bar Drop In (Standard)</p> <p><b>P</b> Pendant Mount (Requires pendant kit)</p> <p><b>R</b> Recessed (Requires recessed mounting kit)</p> <p><b>S</b> Surface Mount / Wall Mount (Requires surface mounting kit)</p>	<p>3000K (+/- -100k)</p> <p>3500K (+/- -100k)</p> <p>4000K (+/- -100k)</p> <p>4500K (+/- -100k)</p> <p>5000K (+/- -100k)</p> <p>5500K (+/- -100k)</p> <p>6000K (+/- -100k)</p> <p>6500K (+/- -100k)</p> <p><b>ER</b> Ergonomic Color Changing Option with user-adjustable CCT range from 2700k to 6500k</p>	<p><b>40W</b> 40 Watts (Standard)</p> <p><b>60W</b> 60 Watts</p>	<p><b>D</b> 0-10V Dimming (Standard)</p> <p><b>N</b> No Dimming required</p> <p><b>DALI</b> - Dali</p>	<p>120V 120V AC/DC (Standard)</p> <p>277V 277V AC/DC</p> <p>347V 347V AC/DC</p>	<p><b>Wet IP 64 rated</b></p> <p><b>Dry</b></p>	<p>Silver / White (Standard)</p> <p>Custom colors available, please inquire.</p>

Note: Not all options are available on all fixtures. Please inquire to be sure your part number is accurate.

**Optical Performance**

Nominal CCT	4000K
Flux (lm)	4200
Efficacy (lm/)	105
W) Power	40
(W) CCT (K)	3989
CRI	92

**Photometry 4000K**

